

## Electric Series Scissor Lifts

# 0812E(2746E)/1012E(3346E)/1212E(4047E)

Complies with ISO/CE/ANSI/AS/CU-TR/KCS standards

### Product Highlights

#### Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions

#### Reduced maintenance costs

- Exclusive open chassis design reduces daily maintenance costs
- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

#### More reliable performance

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding groove designed for anti-scratch

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

# SINOBOOM

**Sinoboom Intelligent Equipment Co Ltd**

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park,  
Changsha, Hunan, China, 410600

🌐 [www.sinoboom.com](http://www.sinoboom.com)

✉ [sales@sinoboom.com](mailto:sales@sinoboom.com)

## Electric Series Scissor Lifts

# 0812E(2746E)/1012E(3346E)/1212E(4047E)

Complies with ISO/CE/ANSI/AS/CU-TR/KCS standards

Model	0812E (2746E)		1012E (3346E)		1212E (4047E)		
Dimensions	Metric	US	Metric	US	Metric	US	
Max Working Height	10.1m	33'2"	12m	39'4.5"	Indoor: 13.9m Outdoor: 11m	Indoor: 45'7" Outdoor: 36'	
A Max Platform Height	8.1m	26'7"	10m	32'10"	Indoor: 11.9m Outdoor: 9m	Indoor: 39' Outdoor: 29'5"	
B Max Horizontal Extension	0.9m	3'	0.9m	3'	0.9m	3'	
C Length-Stored	2.45m	8'	2.45m	8'	2.45m	8'	
D Width-Stored	1.17m	3'10"	1.17m	3'10"	1.17m	3'10"	
Height - stowed	Rail Folded	1.73m	5'8"	1.86m	6'1"	1.98m	6'6"
	E Rail Unfolded	2.36m	7'9"	2.48m	8'2"	2.6m	8'6"
F Wheelbase	1.88m	6'2"	1.88m	6'2"	1.88m	6'2"	
Ground Clearance (Pothole Guard Stowed)	0.1m	4"	0.1m	4"	0.1m	4"	
Ground Clearance (Pothole Guard Deployed)	25mm	0.98"	25mm	0.98"	25mm	0.98"	
Platform Dimensions(LxWxH)	2.30m×1.15m×1.1m (7'6.5"×3'9"×3'7")		2.30m×1.15m×1.1m (7'6.5"×3'9"×3'7")		2.30m×1.15m×1.1m (7'6.5"×3'9"×3'7")		
<b>Performance</b>							
Platform Allowable Occupants (Indoor/ Outdoor)	2 persons/2 persons		2 persons/1 person		Indoors: 2 persons Outdoors: 1 person (outside working height 9m)		
Platform Capacity	450kg	992lbs	320kg	705.6lbs	320kg	705.6lbs	
Drive Speed-Stored	4km/h	2.5mph	4km/h	2.5mph	4km/h	2.5mph	
Drive Speed-Raised	0.8km/h	0.5mph	0.8km/h	0.5mph	0.8km/h	0.5mph	
Elevation Time(Unloaded)	33s~38s		53s~58s		63s~68s		
Descent Time(Unloaded)	35s~40s		40s~45s		44s~49s		
Gradeability	25%		25%		25%		
Turning Radius (Inside/Outside)	0/2.35m	0/7'8.5"	0/2.35m	0/7'8.5"	0/2.35m	0/7'8.5"	
Tilt Rating (Front to Back/Side to Side)	3°/1.5°		3°/1.5°		3°/1.5°		
Tyres-solid	380×125mm	15×5"	380×125mm	15×5"	380×125mm	15×5"	
<b>Power</b>							
Batteries	6V×4/240Ah		6V×4/240Ah		12V×4/300Ah		
Power Source	24V DC		24V DC		24V DC		
Drive Mode	Motor, front-wheel		Motor, front-wheel		Motor, front-wheel		
Charger Input	100~240V AC		100~240V AC		100~240V AC		
Charger Output	30A		30A		30A		
Hydraulic System Capacity	19L	4.2gal)	34L	7.5gal	34L	7.5gal	
<b>Weight</b>							
Weight(Indoor/Outdoor)	2,715kg	5,986lbs	2,815kg	6,206lbs	3,210kg	7,077lbs	
Weight(Indoor Only)	-		2,645kg	5,831lbs	3,100kg	6,834lbs	
Standards Compliance	ISO/CE/ANSI/CSA/AS/CU-TR/KCS						

